

Datalogic® PowerScan® PD9330 Series

Specifications

Dimensions:

(H x L x W): 8.0 x 3.0 x 4.5 in (20.3 x 7.6 x 11.4 cm)

Weight:

280.0 g (9.9 oz)

Display:

LED

Operating Temperature:

-22° F to 122° F (-30° C to 50° C)

Storage Temperature:

-22° F to 122° F (-40° C to 70° C)

Humidity:

5% to 95% non-condensing

Light Source:

Aiming 630 - 680 mm VLD

Communications:

Keyboard wedge, USB or RS-232

Ingress Protection Rating:

IP65

Drop Resistance:

6.6 ft (2 m)

Warranty:

Three-year limited warranty



Standard Features

- IP65 sealing rating
- Durable—tested to 50 drops of 2 m/6.6 ft
- 25 kV electrostatic protection
- Datalogic green spot and loud beeper for good read feedback
- Aladdin® software for configuration

Part Number/Price

Part #	Description	Weight	Price
187055	Scanner, PD7130 YB multi-interface, requires cable - (ordered separately)	4 lb	Consult
187056	Scanner kit, PD7130 YBK2 scanner and RS-232 cable - (included)	4 lb	Consult

Options/Accessories

Part #	Description	Price
114372	Kit, universal mount, Datalogic # 110111 PD7100 Series	Consult
108217	RS-232 cable, CAB-434, 8 ft, nine-pin female coiled, PD7100 Series	Consult
108218	USB cable, CAB-439 for use with PD7130 only	Consult
108219	Keyboard wedge cable, CAB-437, PD7100 Series	Consult
108220	Power supply, desktop 5 volt, 12 W, PD7100 Series	Consult
41276	DB9-M Pin blunt end cable	Consult
Consult	RS-232 coiled 12 ft, CAB 467	Consult
Consult	RS-232 coiled 15 ft, CAB 486	Consult
Consult	USB, 8-0734-08	Consult