

# Minebea Intec Combics 2 Ex

Explosion Proof Digital Weight Indicator



## Specifications

- Load Cell:**  
4 or 6 wire
- Supply Voltage:**  
6V
- Housing:**  
304 stainless steel
- Ingress Protection Rating:**  
IP69K/NEMA Type 4X
- Dimensions:**  
(W x D x H): 11.9 x 7.4 x 3.5 in (302.3 x 188 x 89 mm)
- Operating Temperature:**  
14° F to 104° F (-10° C to 40° C)
- Warranty:**  
Two-year limited warranty  
Accessories: One-year limited warranty
- Approvals:**  
FM approved

## Standard Features

- Amber backlit LCD dot matrix display
- On/Off, Zero, Tare and Print/Data Keys
- Function keys for: Gross/net toggle; three-way unit toggle; 10X higher resolution toggle
- Two header line storage
- Battery charge status display (with connection of battery pack)
- Numeric keypad with two IDs for entering identifier codes and preset tare
- Date/time fully integrated
- GMP printable record
- Three built-in LED checkweighing lights
- Bar graph weighing range indicator
- Application data and totalization memory stored in battery-backed RAM
- Optional barcode scanner for preset tare, reference weight and ID entry
- Requires power supply

## APPROVALS



## Applications Software Pre-installed

- Counting, checkweighing, differential weighing, percentage weighing, gross-net-tare, sorting, net-total, animal weighing.
- Ex approval: FM Class 1,2,3, Division 1, Groups ABCDEFG and temperature class T4.
- Weighbridge connectivity – maximum two precision weighing platforms or load cells, and one precision platform or 1 Combics Ex and one precision platform.
- Power supply can be provided by 110-220 VAC connections and a 24 VDC industrial power module (each suitable for hazardous and safe areas) and a rechargeable battery pack in stainless steel casing.

## Part Number/Price

| RLWS PN | Minebea PN | Description            | Est. Weight | Price   |
|---------|------------|------------------------|-------------|---------|
| 158644  | CAIXS2-U   | IP69K Protection rated | 7 lb        | Consult |

*\*IS power supply or battery pack required*

## Options/Accessories

| RLWS PN | Minebea PN    | Description                                 | Price   |
|---------|---------------|---|---------|
| 46518   | YPS02-XUR     | Power supply, hazardous area, United States | Consult |
| 46517   | YPS02-ZKR     | Power supply, safe area, 65 ft cable        | Consult |
| 103068  | YRB02-X       | Battery pack, 30+ hours (requires 103069)   | Consult |
| 103069  | YRB02-LD      | Charger for battery pack                    | Consult |
| 103054  | YCC02-XR14F02 | Quick disconnect cable, for Zener Barrier   | Consult |
| 155882  | YDI05-ZU1     | Zener Barrier, requires 103054              | Consult |
| 155918  | A19           | 485 interface (IS-X Base)                   | Consult |
| 155919  | M26           | Cable to IS-X                               | Consult |
| 105607  | YDH02CISUS    | Wall mount bracket                          | Consult |