

Aluminum, Environmentally Sealed, NTEP Certified 1:5,000 Class III Single Cell, IP67

Interchangeable Products

- RICE LAKE WEIGHING SYSTEMS
RL1250 page 188
- RICE LAKE WEIGHING SYSTEMS
RLPWM12 page 179
- VPG TEDEA-HUNTLEIGH®
1250 page 360
- HBM®
PW12 page 263



Specifications

- Full Scale Output:**
2.0 mV/V nominal
- Output Resistance:**
350 (± 3) ohm
- Input Resistance:**
415 (± 15) ohm
- Material/Finish:**
Anodized aluminum
- Temperature:**
Compensated range
14°F to 104°F/-10°C to 40°C
Operating range
-40°F to 150°F/-40°C to 65°C
- Safe Overload:**
150% full scale
- Rated Excitation:**
5-10VDC (15VDC Max)
- Seal Type:**
Environmentally sealed, IP67
- Insulation Resistance:**
>5,000 megohms
- Cable Length:**
10 ft (3.1 m)
- Cable Color Code:**
- Green+ Excitation
 - Black.....- Excitation
 - Blue+ Sense
 - Yellow- Sense
 - Red+ Signal
 - White- Signal

Warranty:
Two-year limited warranty

Approvals:



Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	D	E	G	H	J	K	M	N	P
kg/mm												
50-1,000	191.00	8.0	25.00	125.00	25.00	60.00	75.00	82.00	75.00	57.5	85.00	5/16-18 UNC x 15 DP
lb/in												
110.2-2,205	7.52	0.31	0.98	4.92	0.98	2.36	2.95	3.23	2.95	2.26	3.35	5/16-18 UNC x 0.59 DP

Order Information

Load Rating	Part#	Est. Weight	Price
50 kg	191096	5 lb	Consult
75 kg	191097	5 lb	Consult
100 kg	191098	5 lb	Consult
150 kg	191099	5 lb	Consult
200 kg	191100	5 lb	Consult
250 kg	191101	5 lb	Consult
300 kg	191102	5 lb	Consult
500 kg	191103	5 lb	Consult
635 kg	191104	5 lb	Consult
1,000 kg	191105	5 lb	Consult

