

BenchMark® CW-80B

Light-capacity Bench Scales



Standard Features

- 304 stainless steel construction
- LifeGuard™ base design isolates load cell from overloads and shock loads for added durability
- Specially designed adjustable support feet provide exceptional traction and won't scratch surfaces
- NTEP Certified IP67 stainless steel load cell

Specifications

Load Cell, NTEP Certified:

IP67 Stainless steel and environmentally sealed

Output Impedance:

350 Ω

Maximum Overload:

200%

Overload Protection:

Shock-absorbing spider

Cable Length:

10 ft (3 m)

Compensated Temperature Range:

14° F to 104° F (-10° C to 40° C)

Warranty:

Two-year limited warranty

Approvals:

NTEP CC 96-107, Class III, 3000 d, FM,
Measurement Canada AM-5156, Class III 3,000 d

APPROVALS



Measurement
Canada
Approved



Part Number/Price

Part #	Platform Capacity	Dimensions	Est. Weight	Price
35075	6 lb (3 kg)	10 x 10 x 3.15 in	13 lb	Consult
35076	10 lb (5 kg)	10 x 10 x 3.15 in	13 lb	Consult
35077	15 lb (7 kg)	10 x 10 x 3.15 in	13 lb	Consult
35078	30 lb (15 kg)	10 x 10 x 3.15 in	13 lb	Consult
35079	30 lb (15 kg)	12 x 12 x 3.25 in	14 lb	Consult
35080	60 lb (30 kg)	12 x 12 x 3.25 in	14 lb	Consult

Options/Accessories

Part #	Description	Price
N/A	Ball transfer and roller conveyor top	See end of section for details
112044	12 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), 420 plus®. CW-90, CW-90X and 480 Legend Series	Consult
112045	18 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), 420 plus®, CW-90, CW-90X and 480 Legend Series	Consult
64576	Attachment bracket for IQ plus® 210 or 420 plus, 320IS (without battery option), 320IS plus (without battery option) and 480 Legend	Consult
22125	Additional operating manual	Consult

Dimensions

Part#	Capacity	Platform Size (L x W)	L1/W1	H
35075	6 lb (3 kg)	10 x 10 in	10.25 in	3.15 in
35076	10 lb (5 kg)	10 x 10 in	10.25 in	3.15 in
35077	15 lb (7 kg)	10 x 10 in	10.25 in	3.15 in
35078	30 lb (15 kg)	10 x 10 in	10.25 in	3.15 in
35079	30 lb (15 kg)	12 x 12 in	12.25 in	3.25 in
35080	60 lb (30 kg)	12 x 12 in	12.25 in	3.25 in

Note: 1"=25.4 mm

