**CW-90B** 

Light-capacity Bench Scales



# **Specifications**

### **Load Cell, NTEP Certified:**

IP67 Aluminum and environmentally sealed

#### **Output Impedance:**

350Ω

#### **Maximum Overload:**

180 to 200% depending on capacity

#### **Overload Protection:**

Five-point, independently adjusted

# Cable Length:

34 in or 10 ft

#### **Compensated Temperature Range:**

14° F to 104° F (-10° C to 40° C)

### Warranty:

Two-year limited warranty

#### Approvals:

NTEP CC 95-072, Class III 5,000 d Measurement Canada AM-5082, Class III 5,000 d

# **Standard Features**

- 304 stainless steel construction
- Five-point overload protection
- Specially designed adjustable support feet provide exceptional traction and will not scratch surfaces
- IP67 Aluminum environmentally sealed load cell

# **APPROVALS**



Measurement Canada Approved




# Part Number/Price


Part #		Platform Capacity	Dimensions	Est. Weight	Price
10 ft cable	34 in cable				
112599	106137	5 lb (2.5 kg)	10 x 10 x 4.25 in	14 lb	Consult
112601	106138	10 lb (5 kg)	10 x 10 x 4.25 in	14 lb	Consult
112603	106139	25 lb (12.5 kg)	10 x 10 x 4.25 in	14 lb	Consult
112605	106140	25 lb (12.5 kg)	12 x 12 x 4.25 in	17 lb	Consult
112607	106141	50 lb (25 kg)	12 x 12 x 4.25 in	17 lb	Consult
112609	106142	100 lb (50 kg)	12 x 12 x 4.25 in	17 lb	Consult

# **Options/Accessories**

Part #	Description	Price
N/A	Ball transfer and roller conveyor top	See end of section for details
112044	12 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), 420 plus®, CW-90, CW-90X and 480 Legend	Consult
112045**	18 in column for IQ plus® 210, 320IS (without battery option), 320IS plus (without battery option), 420 plus®, CW-90, CW-90X and 480 Legend	Consult

<sup>\*\*</sup> Not recommended for use with scale bases smaller than 12 x 12 in





Drawing Dimensions							
10 in x 10 in							
Α	4.25 in (107.95 mm)	С	10 in (254 mm)				
В	10 in (254 mm)	C1	10.25 in (260.35 mm)				
B1	10.25 in (260.35 mm)						
12 in x 12 in							
Α	4.25 in (107.95 mm)	С	12.0 in (304.8 mm)				
В	12.0 in (304.8 mm)	C1	12.25 (311.15 mm)				
B1	12.25 (311.15 mm)						