



APPROVALS



Available upon request

Picture is a representation of actual product

Dimensions

| Rated Capacity | A | B | C | D | E | F | G | H |
|----------------|-------|------|------|----------|------|------|-------|------|
| kg/mm | | | | | | | | |
| 3-7 | 130.0 | 22.0 | 25.0 | M6 x 1.0 | 25.4 | 15.0 | 106.0 | 12.0 |
| 10-30 | 130.0 | 22.0 | 25.0 | M6 x 1.0 | 30.0 | 15.0 | 106.0 | 12.0 |
| 35 | 130.0 | 22.0 | 25.0 | M6 x 1.0 | 40.0 | 15.0 | 106.0 | 12.0 |
| lb/in | | | | | | | | |
| 6.6-15.4 | 5.12 | 0.87 | 0.99 | M6 x 1.0 | 1.00 | 0.59 | 4.17 | 0.47 |
| 22.0-66.1 | 5.12 | 0.87 | 0.99 | M6 x 1.0 | 1.18 | 0.59 | 4.17 | 0.47 |
| 77.2 | 5.12 | 0.87 | 0.99 | M6 x 1.0 | 1.57 | 0.59 | 4.17 | 0.47 |

Order Information

| Load Rating | | Part# | Est. Weight | Price |
|----------------------|---------|--------|-------------|---------|
| 1.5 ft Cables | | | | |
| 3 kg | 6.6 lb | 41135 | 2 lb | Consult |
| 5 kg | 11.0 lb | 41136 | 2 lb | Consult |
| 7 kg | 15.4 lb | 41137 | 2 lb | Consult |
| 10 kg | 22.0 lb | 41138 | 2 lb | Consult |
| 15 kg | 33.1 lb | 41139 | 2 lb | Consult |
| 20 kg | 44.1 lb | 41140 | 2 lb | Consult |
| 30 kg | 66.1 lb | 41141 | 2 lb | Consult |
| 35 kg | 77.2 lb | 41142 | 2 lb | Consult |
| 10 ft Cables | | | | |
| 3 kg | 6.6 lb | 132269 | 2 lb | Consult |
| 5 kg | 11.0 lb | 132270 | 2 lb | Consult |
| 7 kg | 15.4 lb | 132271 | 2 lb | Consult |
| 10 kg | 22.0 lb | 132272 | 2 lb | Consult |
| 15 kg | 33.1 lb | 132273 | 2 lb | Consult |
| 20 kg | 44.1 lb | 132274 | 2 lb | Consult |
| 30 kg | 66.1 lb | 132275 | 2 lb | Consult |
| 35 kg | 77.2 lb | 132276 | 2 lb | Consult |
| OIML Version | | | | |
| 10 kg | 22.0 lb | 150770 | 2 lb | Consult |
| 15 kg | 33.1 lb | 150771 | 2 lb | Consult |
| 20 kg | 44.1 lb | 150772 | 2 lb | Consult |
| 30 kg | 66.1 lb | 150773 | 2 lb | Consult |

Interchangeable Products

RICE LAKE WEIGHING SYSTEMS

RL1521A..... page 180

VPG CELTRON®

LPS..... page 229

VPG BLH®

C2G1..... —

NMB®

C2G1..... —

Specifications

- Full Scale Output:** 2.0 mV/V
- Output Resistance:** 350 (± 3) ohm
- Input Resistance:** 415 (± 15) ohm
- Material/Finish:** Anodized aluminum
- Temperature:** Compensated range 14°F to 104°F (-10°C to 40°C)
Operating range 0°F to 150°F (-18°C to 65°C)

Seal Type: Environmentally sealed, IP66

Safe Overload: 150% full scale

Rated Excitation: 5- 10 VDC (15 V maximum)

Combined Error: 0.02% full scale

Insulation Resistance: 2,000 megohms

Cable Length: 1.5 ft (0.5 m)
10 ft (3.1 m)

Cable Diameter: 0.140 PVC jacket

Cable Color Code:
Green +Excitation
Black -Excitation
Red +Signal
White -Signal
Blue +Sense
Brown -Sense

Platform Size: 13.78 in x 13.78 in

Warranty: One-year limited warranty

Approvals:
cFMus
NTEP
OIML
Ex (Available upon request)

