

ASC

Stainless Steel, Hermetically Sealed, OIML C3, IP68



Cups not included with load cell, sold separately

APPROVALS



Available upon request

Specifications

- Full Scale Output:**
2.00 +/- 0.02
- Output Resistance:**
700 (± 35) ohm
- Input Resistance:**
700 (± 35) ohm
- Material/Finish:**
Stainless steel
- Temperature:**
Operating range
0°F to 150°F (-18°C to 65°C)
- Seal Type:**
Hermetically sealed, IP68
- Safe Overload:**
150% full scale
- Rated Excitation:**
5 VDC to 20 VDC
- Combined Error:**
0.02% full scale
- Insulation Resistance:**
5,000 megohms
- Cable Diameter:**
0.295 polyurethane jacket
- Cable Length:**
15 m (49.2ft)
- Cable Color Code:**
Green +Excitation
Black -Excitation
White +Signal
Red -Signal
- Warranty:**
One-year limited warranty
- Approvals:**
cFMus
OIML
Ex (available upon request)

Dimensions

Picture is a representation of actual product

Rated Capacity	A	B	C	D	E	F
T/mm						
30-50	150	70	40	87.1	69.1	R200

Order Information

Load Rating	Part#	Est. Weight	Price
OIML			
30T	151312	5 lb	Consult
40T	151313	5 lb	Consult
50T	151314	5 lb	Consult
Options			
Load Cup Set (Upper and Lower)	160452	6 lb	Consult

