



### DIMENSIONS

RATED CAPACITY	H	L	L1	L2	L3	L4	L5	L6	W	W1	W2	T1	T2
<b>108UA:</b> kg/mm 50-1,000	75.0	191.0	41.5	8.0	25.0	125.0	30.0	10.8	75.0	60.0	56.0	M12 Depth30	M8 Depth20
<b>lb/inches</b> (conversion of above dimensions) 110.2-2,204.6	2.95	7.52	1.63	0.31	0.98	4.92	1.18	0.43	2.89	2.36	2.20	M12 Depth1.2	M8 Depth0.8
<b>108UAUN:</b> kg/mm 50-1,000	75.0	191.0	41.5	8.0	25.0	125.0	30.0	10.8	75.0	60.0	56.0	$\frac{1}{2}$ -20 UNF Depth30	$\frac{5}{16}$ -18 UNC Depth20
<b>lb/inches</b> (conversion of above dimensions) 110.2-2,204.6	2.95	7.52	1.63	0.31	0.98	4.92	1.18	0.43	2.89	2.36	2.20	$\frac{1}{2}$ -20 UNF Depth1.2	$\frac{5}{16}$ -18 UNC Depth0.8

### SPECIFICATIONS

<b>Full Scale Output</b>	2.0 mV/V $\pm$ 10%	<b>Recommended Excitation</b>	10V (15V Maximum)
<b>Zero Balance</b>	$\pm$ 0.02 mV/V	<b>Reference Max. Platform Size</b>	750 $\times$ 750 mm
<b>Non-linearity</b>	$<$ $\pm$ 0.017%	<b>Insulation Resistance</b>	$>$ 2 [ 50V DC ] G $\Omega$
<b>Repeatability</b>	$<$ $\pm$ 0.017%	<b>Nominal Temperature Range</b>	-10°C to 40°C / 14°F to 104°F
<b>Hysteresis Error</b>	$<$ $\pm$ 0.017%	<b>Safe Overload</b>	150% of full scale
<b>Creep in 30 min.</b>	$<$ $\pm$ 0.023%	<b>Breaking Overload</b>	300% of full scale
<b>Input Resistance</b>	415 $\Omega$ $\pm$ 15	<b>Seal Type / IP Rating</b>	Environmentally Sealed / IP66
<b>Output Resistance</b>	350 $\Omega$ $\pm$ 3	<b>Cable Color Code</b>	Exc+ Red    Exc- Black Sig+ Green    Sig- White    Shield Bare
<b>Element Material</b>	Aluminum		

### PART NUMBER

Rated Capacity	Part No.	Weight (kg) Approx.
50kg	108UA-50kg	2.7
	108UAUN-50kg	2.7
100kg	108UA-100kg	2.7
	108UAUN-100kg	2.7
150kg	108UA-150kg	2.7
	108UAUN-150kg	2.7
200kg	108UA-200kg	2.7
	108UAUN-200kg	2.7
300kg	108UA-300kg	2.7
	108UAUN-300kg	2.7
500kg	108UA-500kg	2.7
	108UAUN-500kg	2.7
635kg	108UA-635kg	2.7
	108UAUN-635kg	2.7
700kg	108UA-700kg	2.7
	108UAUN-700kg	2.7
1t	108UA-1t	2.7
	108UAUN-1t	2.7

### INTERCHANGEABLE PRODUCTS

108UAUN Manufacturer	Model
ANYLOAD	651BAUN
Coti Global	CG-50
FLINTEC	PCB*
HBM	PW12B
HBM	PW12
Rice Lake	RL1250
Vishay Celtron	LOC
Vishay Revere Transducers	652
Vishay Sensortronics	60060
Vishay TedeA-Huntleigh	1250

\* Flintec PCB is of stainless steel construction, hermetically sealed  
Flintec PCB has 3 version: PCB, PCBB, PCBC, Anyload's 108UAUN is interchangeable to PCB version.

50kg-500kg: NTEP 1:5 000 Class III, Single Cell;  
635kg-1t: NTEP 1:4 000 Class III, Single Cell

50kg-500kg: OIML MAA C5, Y=12 300;  
635kg-1t: OIML MAA C4, Y=4 000